








Model No.	Part No.	Speed & Torque 90 psig Air Pressure*					Overall Length		Weight		Side to Center		Operating Hose		CFM	Square Drive	Tube Capacities*		Chucks	
		Free Speed RPM	Maximum Torque		Minimum Torque												In.	mm	Lbs.	Kg
			In. lbs.	Nm	In. Lbs.	Nm														
 720-2500B	8405541	2500	20	2.29	2	0.23	7-7/8"	198	2.4	1.09	13/16"	20.6	3/8"	7	17	1/4"	1/4"	6.3	1/4"QC	3/8"QC
 720-1800B‡	8405383	1800	27	3.05	2	0.226	7-7/8"	200	2.4	1.09	13/16"	20.6	3/8"	7	17	1/4"	3/8"	9.5	1/4"QC	3/8"QC
 720-550B	8405391	550	75	8.47	2	0.226	8-5/8"	219	2.7	1.23	13/16"	20.6	3/8"	7	17	3/8"	1/2"	12.7	3/8"QC	1/4"QC
 850-1250A	8405399	1066	126	14.2	9.6	1.08	12-1/4"	311	10.5	4.76	1-7/16"	36.5	1/2"	10	48	3/8"	3/4"	19	3/8"QC	1/2"QC
 850-600A	8405398	486	230	26	14.4	1.63	12-1/4"	311	10.5	4.76	1-7/16"	36.5	1/2"	10	48	3/8"	1"	25.4	3/8"QC	1/2"QC

Model No.	Part No.	Speed & Torque 90 psig Air Pressure*					Overall Length		Weight		Side to Center		Operating Hose		CFM	Square Drive	Tube Capacities*		Chucks	
		Free Speed RPM	Maximum Torque		Minimum Torque												In.	mm	Lbs.	Kg
			Ft. lbs.	Nm	Ft. Lbs.	Nm														
 1050-400	8404200	388	26.4	35.8	3.3	4.5	13-5/8"	346	14	6.35	1-15/16"	50	3/4"	13	68	1/2"	1-1/4"	31.7	3/8"QC	1/2Q.C.-3/4"
1550-900	8404290	756	30.7	41.6	4.7	6.4	18"	457	27	12.25	1-15/16"	50	3/4"	13	70	1/2"	1-1/2"	38.1	3/8-1/2"QC	3/4"-1"
1550-250	8404280	220	109.9	149	14.3	19.4	18"	457	27	12.25	1-15/16"	50	3/4"	13	56	3/4"	2-1/2"	63.5	3/4-1"	3/8-1/2"QC

* Varies depending on tube material, gauge, and tube sheet thickness.

‡ Order 8405512 for ordering 720-1800B with 3/8" Q.C. chuck.

 Refer to page 5 for description of Rapid Select.